

排针排母&OPS系列

Pin/Female Header

图片 Photo	系列名称 Series	品名 P/N	产品特征描述 Description	外形尺寸 L*W*H mm	PINS	合高 Height	主体材料 Base	定位柱 Post	端子镀金 Plating	封装方式 Mounting	Logo	包装PCS Package	推荐指数 Rating
	排针	MUP-B1002-01	1.27间距	35.56*5.00*1.50	2*28	3.60	LCP	Y	3U"	SMT	N	800/4000	★★★
	排母	MUP-B9002-01		35.96*4.40*2.10	2*28		LCP	Y	3U"	SMT	Y	1600/8000	★★★★★
	排针	MUP-B1003-01	1.27间距	34.16*5.10*2.00	2*25	4.40	LCP	Y	3U"	SMT	Y	500/2000	★★★
	排母	MUP-B1004-01		32.15*4.40*2.40	2*25		LCP	Y	3U"	SMT	Y	2000/8000	★★★
	排针	MUP-B1003-02	1.27间距	40.51*5.10*2.00	2*30	4.40	LCP	Y	3U"	SMT	Y	500/2000	★★★
	排母	MUP-B1004-03		38.50*4.40*2.40	2*30		LCP	Y	3U"	SMT	Y	2000/8000	★★★
	排针	MUP-B1005-01	1.27间距	31.75*5.50*1.50	2*25	3.60	LCP	Y	3U"	SMT	N	900/4500	★★★
	排母	MUP-B1004-02		32.15*4.40*2.10	2*25		LCP	Y	3U"	SMT	Y	0	★★★
	OPS	MUP-B1007-01	TX24A 版本 高频传输 1.27间距	63.40*15.80*9.00	80	/	PBT	Y	G/F	DIP	N	198/396	★★★★★
	OPS	MUP-B9001-01	TX24A 版本 高频传输 1.27间距	63.40*9.40*9.00	80	/	PBT	Y	5U"	DIP	N	250/1250	★★★★★
	OPS	MUP-B9001-02	TX24A 版本 高频传输 1.27间距	63.40*9.40*9.00	80	/	PA9T	Y	5U"	DIP	N	250/1250	★★★★★